

Innovations in plumbing and heating . . .

1/4 Turn Sillcock - Sweat *patented

Sizes: 1/2" and 3/4"

Description:

The nickel plated Raven Sillcock provides speed and efficiency by utilizing a reliable quarter turn ball valve. Easy on/off operation is assisted by a plastic coated handle. The Sillcock features an oversized flange to allow for a sturdy and clean installation.

Applications:

The Raven Products 1/4 Turn Sillcock will provide the benefits of the ball valve anywhere a conventional "gate valve" sillcock is required.

Models:

1165C

1166C

Features:

- Nickel plated forged brass body
- 1/4 Turn ball valve
- 1/2" or 3/4" Sweat x Hose Bibb model
- Extended threads on Bibb end for secure connection
- Maximum operating temperature 300° F
- Minimum operating temperature 32° F with water, 5° F without water in valve
- Maximum operating pressure 360 PSI
- Low operating torque
- Suitable for a full range of liquids
- Adjustable stem packing gland
- Large lever provides easy on/off operation
- Oversized flange with 2 large screw holes makes installation easy

Materials:

Handle Nut - Stainless Steel
Handle - Stainless Steel
Packing Nut - Stainless Steel

Stem Packing - PTFE **Stem -** Brass

Body - Nickel Plated Brass

Seats - PTFE

Ball - Chrome plated brass

Dimensions:

MODEL	DIMENSIONS		
	A IN.	B IN.	C IN.
1165C - 1/2"	3 1/8"	2 15/16"	2 7/16"
1166C - 3/4"	3 1/8"	2 15/16"	2 7/16"

