

Innovations in plumbing and heating . . .

Multi-Function Circulator Flange with Purge

Sizes: 3/4" - 1 1/2" in Sweat or IPS

Description:


Multi-Function Circulator Flange valves are designed to isolate circulator pumps for easy pump change out or repair. Also allows system purging at same time.

Models

Features:

- · Brass body and flange
- Ball valve design
- Purge ball valve port
- O-ring seal
- Supplied with lever handle, bolts, and gasket
- PTFE seats
- Extended body for soldering
- Provides operation, isolation, and isolation and purge modes

Pressure - 400 PSI WOG





CMFCFWP and

IPSMFCFWP

MODEL	DIMENSIONS				
	A IN.	B IN.	C IN.	D IN.	E IN.
SWEAT:					
34CMFCFWP - 3/4"	3/4"	3 1/4"	3"	3 3/16"	4 1/16"
1CMFCFWP - 1"	1"	3 5/8"	3"	3 3/16"	4 1/16"
114CMFCFWP - 1 1/4"	1 1/4"	4"	3"	3 3/16"	4 1/16"
112CMFCFWP - 1 1/2"	1 1/2"	4 9/16"	3"	3 3/16"	4 1/16"
IPS:					
34IPSMFCFWP - 3/4"	3/4"	3 1/16"	3"	3 3/16"	4 1/16"
1IPSMFCFWP - 1"	1"	3 3/8"	3"	3 3/16"	4 1/16"
114IPSMFCFWP - 1 1/4"	1 1/4"	3 1/2"	3"	3 3/16"	4 1/16"
112IPSMFCFWP - 1 1/2"	1 1/2"	3 15/16"	3"	3 3/16"	4 1/16"